


EPDM STEAM HOSE 230°C



Construction:

Tube: Synthetic rubber EPDM
 Reinforcement: high tensile wire braiding
 Cover: Red or blue, pin pricked smooth (wrapped finish)
 ,EPDM rubber

Application:

The steam hose is used for the saturated steam in chemical

industry, petroleum industry, shipbuilding industry

Characteristic:

- Excellent resistance to high temperature
- Weathering and ozon resistance
- High abrasion resistant cover
- Anti aging, long service life

Item code	I.D		O.D	W.P		B.P		R	L
	mm	inch	mm	bar	psi	bar	psi	mm	kg/m
RSTH2010	10	3/8"	21	17	250	170	2500	50	0.45
RSTH2012	12	1/2"	25	17	250	170	2500	60	0.53
RSTH2016	16	5/8"	28	17	250	170	2500	70	0.6
RSTH2019	19	3/4"	32	17	250	170	2500	80	0.68
RSTH2025	25	1"	39	17	250	170	2500	110	0.9
RSTH2032	32	1 1/4"	46	17	250	170	2500	150	1.3
RSTH2038	38	1 1/2"	54	17	250	170	2500	180	1.6
RSTH2051	51	2"	67	17	250	170	2500	245	2.2
RSTH2064	64	2 1/2"	83	17	250	170	2500	300	3.8
RSTH2076	76	3"	95	17	250	170	2500	400	4.6
RSTH2089	89	3 1/2"	110	17	250	170	2500	500	5.2
RSTH2102	102	4"	124	17	250	170	2500	600	6.5

EPDM STEAM HOSE 170°C

Construction:

Tube: Black EPDM rubber.
 Reinforcement: Multiple layers of heat resistant textile cord.
 Cover: Black EPDM rubber (wrapped finish; pin pricked to prevent blistering).

Temperature: -30°C (-22°F) to +170°C (338°F)

Application:

Hot water hose suitable for many applications in automobile industry, cleaning equipment, cooling systems

Characteristic:

resistant to heat, ozone, anti-freeze, and weathering



Item code	I.D		O.D	W.P	kg	L
	inch	mm	mm	psi	kg/m	m
RSTH1225	1/2"	12	25	100	0.00	15/30/60
RSTH1628	5/8"	16	28	100	0.00	15/30/60
RSTH1932	3/4"	19	32	100	0.00	15/30/60
RSTH2539	1"	25	39	100	0.00	15/30/60
RSTH3854	1-1/2"	38	54	100	0.00	15/30/60
RSTH5167	2"	51	67	100	0.00	15/30/60