

TEXTILE REINFORCED AIR HOSE



Construction:

Tube: NR & SBR synthetic rubber, black color.

Reinforcement: 1ply or 2ply high tensile polyester thread braiding, Multi ply high tensile fabric

Cover: NR & SBR synthetic rubber, smooth or wrapped surface, black, yellow, red available

Application:

Mainly used for conveying of air, inert gas and water in mining, construction, engineering, shipbuilding, steel

production etc.

Temperature:

-40°C (-104 °F) to 70°C +158 °F

Characteristics:

- Oil mist resistant tube
- Anti-aging synthetic rubber
- Weather and ozone resistant
- Excellent abrasion resistance

AIR HOSE WRAPPED SURFACE 300PSI

Item Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
CAH-005	3/16"	4.8	12	20	300	60	900	100	330
CAH-006	1/4"	6.4	13	20	300	60	900	100	330
CAH-008	5/16"	7.9	15	20	300	60	900	100	330
CAH-010	3/8"	9.5	17	20	300	60	900	100	330
CAH-012	1/2"	12.7	23	20	300	60	900	100	330
CAH-019	3/4"	19.1	30	20	300	60	900	100	330
CAH-025	1"	25.4	37	20	300	60	900	100	330
CAH-032	1-1/4"	31.8	46	20	300	60	900	60	200
CAH-038	1-1/2"	38.1	52	20	300	60	900	60	200
CAH-050	2"	50.8	68	20	300	60	900	60	200
CAH-064	2-1/2"	63.5	80	20	300	60	900	60	200
CAH-076	3"	76.2	92	20	300	60	900	60	200
CAH-102	4"	101.6	120	20	300	60	900	60	200