

## RUBBER TWIN WELDING HOSE 300 PSI

**Construction:**

Tube : Black, smooth, synthetic rubber  
 Reinforcement: High strength synthetic yarn braiding  
 Cover: Blue/green/red, smooth, synthetic rubber

**Application:**

Designed for welding, cutting and allied processes. Specific welding hose carting for oxygen, carbon dioxide, nitrogen, argon and fuel gases including acetylene, natural gas, methane and propane available upon request.

**Temperature:** -32°C (-90 °F ) to 80°C (+176 °F)

**Characteristics:**

- Anti abrasion smooth cover
- Weather and ozone resistant cover
- Flexible, light weight, less distortion.



Item code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
TWH005	3/16"	4.8+4.8	12+12	20	300	60	900	100	330
TWH006	1/4"	6.4+6.4	13+13	20	300	60	900	100	330
TWH008	5/16"	7.9+7.9	15+15	20	300	60	900	100	330
TWH810	5/16"+3/8"	7.9+9.5	15+17	20	300	60	900	100	330
TWH010	3/8"	9.5+9.5	17+17	20	300	60	900	100	330

## RUBBER LPG/ PROPAN/GAS HOSE 300 PSI

**Construction:**

Tube: Black, smooth, Nitrile synthetic rubber  
 Reinforcement: High strength synthetic yarn braiding  
 Cover: orange/red/black, smooth, synthetic rubber NBR or chloroprene CR

**Application:**

For commercial and family gas cooker oven, the connection of gas system of industrial device. Transport media: LPG, CNG, CH4 etc

**Temperature:** -32°C (-90 °F ) to 80°C (+176 °F)

**Characteristics:**

- Anti abrasion smooth cover
- Weather and ozone resistant cover
- Flexible, light weight, less distortion
- Certification: ISO3821, EN559



Item code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	PSI	bar	PSI	m	ft
GASH005	3/16"	4.8	12	20	300	60	900	100	330
GASH006	1/4"	6.4	13	20	300	60	900	100	330
GASH008	5/16"	7.9	15	20	300	60	900	100	330
GASH010	3/8"	9.5	17	20	300	60	900	100	330
GASH012	1/2"	12.7	21	20	300	60	900	100	330