

RUBBER OXYGEN /ACETYLENE HOSE 300 PSI

Construction:

Tube:Black, smooth, synthetic rubber

Reinforcement:High strength synthetic plies

Cover:Blue/green/red, smooth, synthetic rubber

Application:

Designed for welding, cutting and allied processes. Specific welding hose cartering for oxygen, carbon dioxide, nitrogen, argon and fuel gases including acetylene, natural gas, methane and propane available upon request.

Temperature:

-32°C (-90 °F) to 80°C (+176 °F)

Characteristics:

- Anti abrasion smooth cover
- Weather and ozone resistant cover
- Flexible,light weight,less distortion



Oxygen Hose 300PSI

Item code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
OXYH005	3/16"	4.8	12	20	300	60	900	100	330
OXYH006	1/4"	6.4	13	20	300	60	900	100	330
OXYH008	5/16"	7.9	15	20	300	60	900	100	330
OXYH010	3/8"	9.5	17	20	300	60	900	100	330
OXYH012	1/2"	12.7	21	20	300	60	900	100	330
OXYH016	5/8"	15.9	26	20	300	60	900	100	330
OXYH019	3/4"	19.1	29	20	300	60	900	100	330
OXYH025	1"	25.4	36	20	300	60	900	100	330

Acetylene Hose 300PSI

Item code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
ACEH005	3/16"	4.8	12	20	300	60	900	100	330
ACEH006	1/4"	6.4	13	20	300	60	900	100	330
ACEH008	5/16"	7.9	15	20	300	60	900	100	330
ACEH010	3/8"	9.5	17	20	300	60	900	100	330
ACEH012	1/2"	12.7	21	20	300	60	900	100	330
ACEH016	5/8"	15.9	26	20	300	60	900	100	330
ACEH019	3/4"	19.1	29	20	300	60	900	100	330
ACEH025	1"	25.4	36	20	300	60	900	100	330