

# ROLLER SKATES

## Model: RSA



**Shifting skate** can be used wherever heavy objects have to be moved. The load can be lifted using either the roller crowbar or a jack, allowing the skates to be easily positioned. The large diameter sealed nylon roller ensure ease of movement and spread the load, protecting high quality floors from damage caused by high pointloads and oil/grease contamination. The skates are maintenance free and are fitted with handles for ease of carrying and positioning.

**Turnable with bearings; Friction Coefficient: 0.15 to 0.25**

Product code	Capacity (Ton)	Wheel NO.	Length (mm)	Width (mm)	Height (mm)	Weight (Kg)
RSA 04	6	4	300	225	110	13.15
RSA 06	8	6	400	225	110	15.80
RSA 08	12	8	500	225	110	25.91
RSA 12	18	12	500	313	110	40.93

Minimum turning circle is 3 meters

## Model: RSO



**Fixed skate type; Friction Coefficient: 0.15 to 0.25**

Product code	Capacity (Ton)	Wheel NO.	Length (mm)	Width (mm)	Height (mm)	Weight (Kg)
RSO 04	6	4	300	225	100	11.89
RSO 06	8	6	400	225	100	14.55
RSO 08	12	8	500	225	100	24.65
RSO 12	18	12	500	313	100	39.67

Minimum turning circle is 3 meters